


## Ceiling recessed downlight

8 314 156 059

19 W, 1863 lm, 3000 K warm white,
wide beam 50°
Remote control gear unit essentially required, see data sheet with accessories






Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Remote control gear unit essentially required, see data sheet with accessories

### Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, luminaire fixed using stainless steel spring loaded clamps, clamping range in hollow ceilings 12-42 mm, aperture for installation Ø 125 mm, connecting terminal: 3 pole, highly efficient faceted and coated rotationally symmetrical reflector, 1 m cable, remote driver required, CRI > 80, max 2 SDCM, service life L90/B10 > 50.000 h, Beam angle (FWHM): 50°, luminous flux: 1863 lm, wattage: 19 W, delivered lumens 97 lm/W, protection type IP65, protection class III, impact resistance IK08, dimensions: Ø 140 mm, width 95 mm, weight 1 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

III IP65 IK08

## Specification

| | | | |
|---|---|---|---|
| Wattage | 19 W | Beam angle (FWHM) | 50° |
| Delivered lumens | 97 lm/W | Housing colour | silver grey |
| Light source | LED 3000 K | Protection type | IP65 |
| Color Rendering Index | CRI > 80 | Protection class | III |
| Colour tolerance | max 2 SDCM | Impact resistance | IK08 |
| Lifetime ta 25° C | L90/B10 > 50.000 h | Dimensions | Ø 140 mm, width 95 mm |
| Control gear | on / off / DALI | Weight | 1,00 kg |
| Input voltage AC | With remote control gear unit See accessories | Max. ambient temperature ta | 40° |
| Input voltage DC | | | |
| Voltage protection | 2 kV L/N \| 4 kV L/PE | | |
| Luminaires per B16A / C16A | 50 / 85 | | |