



**Ecoline Mini modular system
luminaire, middle**

8 769 356 009
15 × 1,8 W, 1463 lm, 3000 K warm white,
wall washer 20° / 88° ,



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of extruded aluminum and corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, polycarbonate cover, with partial frosting for uniform light diffraction, silicon gasket, with connection coupling and 3-pin connector on the left and right, tilt range: 220°, connecting terminal: 3 pole, highly efficient optics made of transparent thermoplastic for precise lighting tasks , integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L90/B10 > 50.000 h, Beam angle (FWHM): 20° / 88°, luminous flux: 1463 lm, wattage: 26 W, delivered lumens 56 lm/W, protection type IP65, protection class I, impact resistance IK10, windage area 0,059 m², dimensions (L×H×W): 1507 × 43 × 40 mm, weight 3 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK10

Specification

Wattage	26 W	Beam angle (FWHM)	20° / 88°
Delivered lumens	56 lm/W	Housing colour	silver grey
Light source	LED 3000 K	Power supply cable	Ø 5 – 9 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	max 2 SDCM	Protection class	I
Lifetime ta 25° C	L90/B10 > 50.000 h	Impact resistance	IK10
Control gear	on / off	Windage area	0,059m²
Input voltage AC	220 – 240 V	Dimensions	1507 × 43 × 40 mm
Input voltage DC	195 – 250 V	Weight	3,00 kg
Voltage protection	2 kV L/N 4 kV L/PE	Max. ambient temperature ta	50°