


Ecoline modular system luminaire, left

8 797 255 089 12 × 2,5 W, 2249 lm, 4000 K neutral white, asymmetrical 36° / 64° L1 = 1242 mm





Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification

Wattage 30 W Delivered lumens 75 lm/W Light source LED 4000 K Color Rendering Index CRI > 80 max 2 SDCM Colour tolerance Lifetime ta 25° C L90/B10 > 50.000 h Control gear on / off Input voltage AC 110 – 240 V Input voltage DC 195 - 255 V 2 kV L/N | 4 kV L/PE Voltage protection Luminaires per B16A / C16A 50 / 85

Specification text

housing made of extruded aluminum and corrosion-resistant die-cast aluminum AlSi 1 2, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, UV stabilised, impact-resistant polycarbonate cover with partial frosting for uniform light diffraction, silicon gasket, closure with 2 stainless steel screws, with stainless steel coupling on right side, tilt range: 220°, cable gland: M20, connecting terminal: 3 pole, highly efficient optics made of transparent thermoplastic for precise lighting tasks , CRI > 80, max 2 SDCM, service life L90/B10 > 50.000 h, luminous flux: 2249 lm, wattage: 30 W, delivered lumens 75 lm/W, protection type IP65, protection class I, impact resistance IK10, windage area 0,07 m², dimensions (L×H×W): 1242 × 58 × 54 mm, weight 3.4 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



Housing colour	silver grey
Power supply cable	Ø 6 - 10 mm
Protection type	IP65
Protection class	I
Impact resistance	IK10
Windage area	0,07m²
Dimensions	1242 × 58 × 54 mm
Weight	3,40 kg
Max. ambient temperature ta	40°

Technical and formal changes reserved, product photos are exmplary. As of

Willy Meyer+Sohn GmbH+Co. KG | Stemmessiepener Weg 5 | 58675 Hemer | Germany | info@meyer-lighting.com | www.meyer-lighting.com