


## Fluxa B

8 275 145 009 For metal halide lamps (HIT-DE)







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, closure with 2 stainless steel screws, 230 mm arm, 2 drilled holes Ø 10.5 mm, spacing 58 mm, cable gland: M20, connecting terminal: 3 pole, high gloss asymmetrical aluminum reflector, integral ballast and ignitor, LPF, HPF available on request, luminous flux: 20000 lm, wattage: 250 W, delivered lumens 72 lm/W, protection type IP54, protection class I, impact resistance IK09, windage area 0,19 m², dimensions (L×H×W): 730 × 185 × 335 mm, weight 14.7 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP 54 IK 09

## Specification

Wattage 250 W
Delivered lumens 72 lm/W
Light source LED 4000 K
Control gear on / off

Housing colour black RAL 7021

Power supply cable  $\emptyset$  8 – 15 mm

Protection type IP54

Protection class I
Impact resistance IK09
Windage area 0,19m²

Dimensions  $730 \times 185 \times 335 \text{ mm}$ 

Weight 14,70 kg