



Fluxa A

8 286 046 169

63 W, 6387 lm, 3000 K warm white, DALI, asymmetrical $55\,^{\circ}$







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, with prismatic glass

for reduced glare, silicon gasket, closure with 4 stainless steel screws, powder coated aluminum mounting bracket with tilt scale: 4 holes Ø 8.5 mm, spacing 70 mm (120 mm), 2 drilled holes Ø 10 mm, spacing 200 mm, 1 centre hole Ø 22 mm, tilt range: 210°, cable gland: M20, connecting terminal: 5 pole, highly efficient anodized rotationally symmetrical reflector with matt finish, integral driver (DALI / Step Dim / Astro Dim), CRI > 70, max 2 SDCM, service life L90/B10 > 50.000 h, luminous flux: 6387 lm, wattage: 63 W, delivered lumens 101 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area 0,11 m², dimensions (L×H×W): 380 × 131 × 280 mm, weight 6.2 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.





Windage area

IP67 IK08

Specification

Wattage 63 W 101 lm/W Delivered lumens Light source LED 3000 K Color Rendering Index CRI > 70 max 2 SDCM Colour tolerance L90/B10 > 50.000 h Lifetime ta 25° C Control gear DALI Input voltage AC 170 - 260 V Input voltage DC 176 – 276 V

Voltage protection 6 kV L/N | 10 kV L/PE

Luminaires per B16A / C16A 12 / o

Housing colour

Power supply cable

Protection type

Protection class

Impact resistance

| Black RAL 7021
| 8 - 15 mm

| P67
| Protection class
| IKO8

Dimensions $380 \times 131 \times 280 \text{ mm}$

0,11m²

Weight 6,20 kg Max. ambient temperature ta 45°