



Fluxa A

8 287 045 159 2×31 W, 7032 lm, 4000 K neutral white, DALI,







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, closure with 4 stainless steel screws, powder coated aluminum mounting bracket with tilt scale: 4 holes Ø 8.5 mm, spacing 70 mm (120 mm), 2 drilled holes Ø 10 mm, spacing 200 mm, 1 centre hole \varnothing 22 mm, tilt range: 210°, cable gland: M20, connecting terminal: 5 pole, highly efficient anodized rotationally symmetrical reflector with matt finish, integral driver (DALI / Step Dim / Astro Dim), CRI > 70, max 2 SDCM, service life L90/B10 > 50.000 h, Beam angle (FWHM): 72° / 122°, luminous flux: 7032 lm, wattage: 62 W, delivered lumens 113 lm/W, protection type IP67, protection class I, impact resistance IKo8, windage area 0,11 m², dimensions (L×H×W): $380 \times 131 \times 280$ mm, weight 6.2 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.





IP 67 IK 08

Specification

Wattage 62 W Delivered lumens 113 lm/W Light source LED 4000 K Color Rendering Index CRI > 70 Colour tolerance max 2 SDCM Lifetime ta 25° C L90/B10 > 50.000 h DALI Control gear Input voltage AC 170 - 260 V Input voltage DC 176 – 276 V 6 kV L/N | 10 kV L/PE Voltage protection Luminaires per B16A / C16A 12/0

72° / 122° Beam angle (FWHM) Housing colour black RAL 7021 Power supply cable Ø 8 – 15 mm Protection type IP67 Protection class Impact resistance IKo8 Windage area O,11m² Dimensions 380 × 131 × 280 mm Weight 6,20 kg Max. ambient temperature ta 45°