


## Fluxa BG

8 288 156 079

 $_{\rm 2}$  × 70 W, 10533 lm, 3000 K warm white, wide beam 61  $^{\circ}$  / 133  $^{\circ}$ 







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, with prismatic glass

for reduced glare, silicon gasket, closure with 4 stainless steel screws, adjustable bracket assembly: 2 drilled holes  $\varnothing$  8.5 mm, spacing 64 mm, 2 drilled holes  $\varnothing$  8.5 mm, spacing 56 mm, tilt range: 15°, cable gland: M20, connecting terminal: 3 pole, highly efficient anodized rotationally symmetrical reflector with matt finish, integral driver (AC/DC), CRI > 70, max 2 SDCM, service life L90/B10 > 50.000 h,

Beam angle (FWHM): 61° / 133°, luminous flux: 10533 lm, wattage: 139 W, delivered lumens 76 lm/W, protection type IP65, protection class I, impact resistance IKo9, windage area 0,16 m², dimensions (L×H×W): 450 × 157 × 335 mm, weight 9.7 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP65 IK09

## Specification

Wattage 139 W Delivered lumens 76 lm/W Light source LED 3000 K Color Rendering Index CRI > 70 max 2 SDCM Colour tolerance L90/B10 > 50.000 h Lifetime ta 25° C on / off Control gear Input voltage AC 220 - 240 V 195 – 255 V Input voltage DC Voltage protection 6 kV L/N | 10 kV L/PE Luminaires per B16A / C16A 5/10

61° / 133° Beam angle (FWHM) Housing colour silver grey Power supply cable  $\emptyset$  8 - 15 mm IP65 Protection type Protection class Impact resistance IK09 Windage area  $0,16m^2$ Dimensions 450 × 157 × 335 mm Weight 9,70 kg 40° Max. ambient temperature ta