




Halogen floodlight

8 530 091 009



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

unpainted, Colour: unpainted , all exterior parts are stainless steel, 2 stainless steel clamps, mounting bracket aluminum: 4 drilled holes Ø 8.5 mm, spacing 70 mm (140 mm), 1 centre hole Ø 8.5 mm, tilt range: 100°, cable gland: PG11, connecting terminal: 3 pole, axially symmetrical aluminum reflector, Beam angle (FWHM): 72°, luminous flux: 9500 lm, wattage: 500 W, delivered lumens 19 lm/W, protection type IP54, protection class I, impact resistance IK07, dimensions (LxHxW): 240 x 120 x 210 mm, weight 1.57 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP 54 IK07

Specification

Wattage	500 W	Beam angle (FWHM)	72°
Delivered lumens	19 lm/W	Housing colour	unpainted
Control gear	on / off	Protection type	IP54
		Protection class	I
		Impact resistance	IK07
		Dimensions	240 x 120 x 210 mm
		Weight	1,57 kg