




Halogen floodlight

8 539 045 009



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, stainless steel release fastener, stainless steel mounting bracket: 2 holes \varnothing 9 mm, spacing 70 mm, 1 centre hole \varnothing 10.5 mm, tilt range: 100°, cable gland: PG13,5, connecting terminal: 3 pole, axially symmetrical aluminum reflector, Beam angle (FWHM): 38°, luminous flux: 1860 lm, wattage: 100 W, delivered lumens 19 lm/W, protection type IP65, protection class III, impact resistance IK07, dimensions (L×H×W): 210 × 110 × 245 mm, weight 1.47 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

III IP65 IK07

Specification

Wattage	100 W	Beam angle (FWHM)	38°
Delivered lumens	19 lm/W	Housing colour	black RAL 7021
Control gear	on / off	Protection type	IP65
		Protection class	III
		Impact resistance	IK07
		Dimensions	210 × 110 × 245 mm
		Weight	1,47 kg