





## **Halogen floodlight**

8 539 061 009







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## **Specification text**

polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, stainless steel release fastener, stainless steel mounting bracket: 2 holes  $\varnothing$  9 mm, spacing 70 mm, 1 centre hole  $\varnothing$  10.5 mm, tilt range: 100°, cable gland: PG13,5, connecting terminal: 3 pole, axially symmetrical aluminum reflector, Beam angle (FWHM): 34°, luminous flux: 9500 lm, wattage: 500 W, delivered lumens 19 lm/W, protection type IP65, protection class I, impact resistance IK07, dimensions (L×H×W): 210 × 110 × 245 mm, weight 1.42 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP65 IK07

## Specification

Wattage 500 W
Delivered lumens 19 lm/W
Control gear on / off

Beam angle (FWHM)  $34^{\circ}$ 

Housing colour white RAL 9002 Power supply cable  $\emptyset$  5 – 13 mm

Protection type IP65
Protection class I
Impact resistance IK07

Dimensions 210 × 110 × 245 mm

Weight 1,42 kg