




Metaspace

8 215 347 389

 $6 \times 6,3$ W, 3522 lm, 2700 K warm white, Zhaga 18 - up,

asymmetrical wide beam 64° / 133°







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered high effiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 5 stainless steel screws, with pole top fitter for 1 luminarie for poles Ø 60/76 mm, fastening with 4 set screws M8, cable gland: M20, with 8 m cable Ho7RN-F3G1, connecting terminal: 3 pole, highly efficient metallized PC reflector, integral driver (AC/DC), CRI > 80, 3, service life L80/B20 > 50.000 h,

Beam angle (FWHM): 64° / 133° , luminous flux: 3522 lm, wattage: 38 W, delivered lumens 93 lm/W, protection type IP65, protection class I, impact resistance IKo8, windage area 0.056 m², dimensions: \emptyset 376 mm, width 112 mm, weight 5.1 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.





1P65 1K08

Specification

Wattage 38 W Delivered lumens 93 lm/W LED 2700 K Light source CRI > 80 Color Rendering Index Colour tolerance Lifetime ta 25° C L80/B20 > 50.000 h Control gear Zhaga 18 - oben Input voltage AC 220 - 240 V Input voltage DC 220 - 240 V 6 kV L/N | 10 kV L/PE Voltage protection

Luminaires per B16A / C16A 20 / 33

Beam angle (FWHM) 64° / 133° Housing colour black RAL 7021 Protection type IP65 Protection class Impact resistance **IK**08 Windage area 0,056m² Dimensions Ø 376 mm, width 112 mm Weight 5,10 kg 40° Max. ambient temperature ta