





Metaspace

8 215 352 189 24 × max. W27 W, 2249 lm, 2200 K – 3000 K tunable white, DALI, asymmetrical wide beam 64° / 133°







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered high effiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 5 stainless steel screws, with pole top fitter for 1 luminarie for poles Ø 60/76 mm, fastening with 4 set screws M8, cable gland: M20, with 8 m cable Ho5RN-F3G1, connecting terminal: 3 pole, highly efficient metallized PC reflector, integral driver (DALI), CRI > 80, Beam angle (FWHM): 64° / 133°, luminous flux: 2249 lm, wattage: 27 W, delivered lumens 82 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,056 m², dimensions: Ø 376 mm, width 112 mm, weight 5.1 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.





IP65 IK08

Specification

Wattage 27 W Beam angle (FWHM) 64° / 133° Delivered lumens 82 lm/W Housing colour silver grey Light source LED 2200 K - 3000 K Protection type IP65 Color Rendering Index CRI > 80 Protection class Control gear DALI Impact resistance **IK**08 Input voltage AC 220 - 240 V Windage area 0,056m² Input voltage DC 176 – 280 V Dimensions Ø 376 mm, width 112 mm 6 kV L/N | 10 kV L/PE Weight Voltage protection 5,10 kg 45° Luminaires per B16A / C16A Max. ambient temperature ta 35 / 58