


Metaspacer

8 217 366 549
6 × 6,3 W, 3741 lm, 3000 K warm white, Zhaga 18 -
up / down,
asymmetrical beam 63°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered high efficiency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 5 stainless steel screws, with pole top fitter for 1 luminaire for poles Ø 60/76 mm, fastening with 4 set screws M8, cable gland: M20, with 8 m cable Ho7RN-F3G1, connecting terminal: 3 pole, highly efficient metallized PC reflector, integral driver (AC/DC), CRI > 80, 3, service life L80/B20 > 50.000 h, luminous flux: 3741 lm, wattage: 38 W, delivered lumens 99 lm/W, protection type IP65, protection class II, impact resistance IK08, windage area 0,056 m², dimensions: Ø 376 mm, width 112 mm, weight 5.1 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



Specification

Wattage	38 W
Delivered lumens	99 lm/W
Light source	LED 3000 K
Color Rendering Index	CRI > 80
Colour tolerance	3
Lifetime ta 25° C	L80/B20 > 50.000 h
Control gear	Zhaga 18 - oben / unten
Input voltage AC	220 – 240 V
Input voltage DC	220 – 240 V
Voltage protection	6 kV L/N 10 kV L/PE
Luminaires per B16A / C16A	20 / 33

Housing colour	white RAL 9002
Protection type	IP65
Protection class	II
Impact resistance	IK08
Windage area	0,056m²
Dimensions	Ø 376 mm, width 112 mm
Weight	5,10 kg
Max. ambient temperature ta	40°