




Monospace

8 250 455 109 2 × 55 W, 8339 lm, 4000 K neutral white, DALI, Comfort Optic 71° / 139°







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, tempered high efflency safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 4 stainless steel screws, with pole top fitter for 2 luminaires for poles Ø 60/76 mm, 3 M8 grub screws, tilt range: 7°, cable gland: M20, with 2x 8 m cable Ho5RN-F5G1, connecting terminal: 5 pole, micro-prism optic directs light under defined angles and achieves, together with shielded LEDs, perfect glare control , integral driver (DALI), CRI > 80, 3 SCDM, service life L80/B20 > 50.000 h,

Beam angle (FWHM): 71 ° / 139°, luminous flux: 8339 lm, wattage: 110 W, delivered lumens 76 lm/W, protection type IP67, protection class I, impact resistance IKo8, windage area 0,063 m², dimensions (L×H×W): 924 × 67 × 308 mm, weight 9.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.





IP67 IK08

Specification

Wattage 110 W

Delivered lumens 76 lm/W

Light source LED 4000 K

Color Rendering Index CRI > 80

Colour tolerance 3 SCDM

Lifetime ta 25° C L80/B20 > 50.000 h

Control gear DALI

Beam angle (FWHM)

71° / 139°

Housing colour

Power supply cable

Protection type

Protection class

Impact resistance

Windage area

Dimensions

71° / 139°

85 - 14 mm

Prof

1P67

IK08

Woodsm²

924 × 67 × 308 mm

Weight

98 kg

Weight 9,80 kg
Max. ambient temperature ta 35°