



Monospot+

8 996 366 159

53 W, 4523 lm, 3000 K warm white, DALI, wide beam 53°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 3 stainless steel screws, for installation on poles Ø 60 - 100 mm, tiltable base made of powder coated aluminium, 2 drilled holes Ø 8.5 mm, spacing 42 mm, 1 centre hole Ø 20 mm, tilt range: tilt range 33°, swivel range 360°, cable gland: M20, connecting terminal: 5 pole, highly efficient aluminum reflector, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L80/B10 > 50.000 h, Beam angle (FWHM): 53°, luminous flux: 4523 lm, wattage: 53 W, delivered lumens 85 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,059 m², dimensions: Ø 194 mm, width 232 mm, weight 3.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08

Specification

Wattage	53 W	Beam angle (FWHM)	53°
Delivered lumens	85 lm/W	Housing colour	white RAL 9002
Light source	LED 3000 K	Power supply cable	Ø 6 – 13 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	max 2 SDCM	Protection class	I
Lifetime ta 25° C	L80/B10 > 50.000 h	Impact resistance	IK08
Control gear	DALI	Windage area	0,059m ²
Input voltage AC	220 – 240 V	Dimensions	Ø 194 mm, width 232 mm
Input voltage DC	220 – 240 V	Weight	3,80 kg
Voltage protection	2 kV L/N 2 kV L/PE	Max. ambient temperature ta	35°
Luminaires per B16A / C16A	23 / 39		