



## Monospot S3

8 993 265 159

28 W, 2438 lm, 4000 K neutral white, DALI, wide beam (with indirect reflector) 84°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 3 stainless steel screws, for installation on poles  $\varnothing$  60 - 100 mm, tiltable base made of powder coated aluminum, 2 drilled holes  $\varnothing$  9 mm, spacing 95 mm, 1 centre hole  $\varnothing$  13.5 mm, tilt range: 90°, 360° adjustable, cable gland: M16, connecting terminal: 5 pole, highly efficient faceted rotationally symmetrical reflector, integral, dimmable driver (DALI), CRI > 80, max 3 SDCM, service life L80/B20 > 50.000 h, Beam angle (FWHM): 84°, luminous flux: 2438 lm, wattage: 28 W, delivered lumens 86 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area 0,016 m<sup>2</sup>, dimensions:  $\varnothing$  148 mm, width 100 mm, weight 1.7 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



IP67 IK08

## Specification

|                            |                      |                             |                                    |
|----------------------------|----------------------|-----------------------------|------------------------------------|
| Wattage                    | 28 W                 | Beam angle (FWHM)           | 84°                                |
| Delivered lumens           | 86 lm/W              | Housing colour              | white RAL 9002                     |
| Light source               | LED 4000 K           | Power supply cable          | $\varnothing$ 5 - 9 mm             |
| Color Rendering Index      | CRI > 80             | Protection type             | IP67                               |
| Colour tolerance           | max 3 SDCM           | Protection class            | I                                  |
| Lifetime ta 25° C          | L80/B20 > 50.000 h   | Impact resistance           | IK08                               |
| Control gear               | DALI                 | Windage area                | 0,016m <sup>2</sup>                |
| Input voltage AC           | 220 - 240 V          | Dimensions                  | $\varnothing$ 148 mm, width 100 mm |
| Input voltage DC           | 220 - 240 V          | Weight                      | 1,70 kg                            |
| Voltage protection         | 2 kV L/N   4 kV L/PE | Max. ambient temperature ta | 35°                                |
| Luminaires per B16A / C16A | 50 / 85              |                             |                                    |