




Monospot 4

8 904 059 059
49 W, 1937 lm, RGBW (3000 K) DMX,
wide beam 57°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 3 stainless steel screws, bracket: 2 long holes Ø 7 mm, spacing 40-60 mm, 1 centre hole Ø 21 mm, tilt range: 180°, cable gland: M20, connecting terminal: 6 pole, highly efficient faceted rotationally symmetrical reflector, integral driver (AC/DC), Beam angle (FWHM): 57°, luminous flux: 1937 lm, wattage: 49 W, delivered lumens 40 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area 0,075 m², dimensions: Ø 215 mm, width 240 mm, weight 4.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



Specification

| | | | |
|----------------------------|-------------------|-----------------------------|------------------------|
| Wattage | 49 W | Beam angle (FWHM) | 57° |
| Delivered lumens | 40 lm/W | Housing colour | silver grey |
| Light source | LED RGBW (3000 K) | Power supply cable | Ø 6 – 13 mm |
| Control gear | DMX | Protection type | IP67 |
| Input voltage AC | 120 – 277 V | Protection class | I |
| Input voltage DC | 120 – 250 V | Impact resistance | IK08 |
| Luminaires per B16A / C16A | 22 / 22 | Windage area | 0,075m² |
| | | Dimensions | Ø 215 mm, width 240 mm |
| | | Weight | 4,80 kg |
| | | Max. ambient temperature ta | 35° |