



Monospot Mini

8 900 046 039
3 W, 130 lm, 3000 K warm white,
linear, horizontal



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification

| | | | |
|-----------------------|------------|-------------------|----------------------|
| Wattage | 3 W | Housing colour | black RAL 7021 |
| Delivered lumens | 43 lm/W | Protection type | IP65 |
| Light source | LED 3000 K | Protection class | I |
| Color Rendering Index | CRI > 80 | Impact resistance | IK08 |
| Control gear | on / off | Windage area | 0,006m² |
| | | Dimensions | Ø 75 mm, width 81 mm |
| | | Weight | 0,60 kg |

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 2 stainless steel screws, 1 elongated hole Ø 7 mm, spacing 15 mm, 1 centre hole Ø 8.5 mm, tilt range: 180°, cable gland: M16, connecting terminal: 3 pole, precise PMMA optics, integral driver (AC/DC), CRI > 80, luminous flux: 130 lm, wattage: 3 W, delivered lumens 43 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,006 m², dimensions: Ø 75 mm, width 81 mm, weight 0.6 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65 IK08