



### Monospot Mini

8 900 065 039  
3 W, 140 lm, 4000 K neutral white,  
linear, horizontal



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

### Specification

Wattage	3 W	Housing colour	white RAL 9002
Delivered lumens	47 lm/W	Protection type	IP65
Light source	LED 4000 K	Protection class	I
Color Rendering Index	CRI > 80	Impact resistance	IK08
Control gear	on / off	Windage area	0,006m²
		Dimensions	Ø 75 mm, width 81 mm
		Weight	0,60 kg

### Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 2 stainless steel screws, 1 elongated hole Ø 7 mm, spacing 15 mm, 1 centre hole Ø 8.5 mm, tilt range: 180°, cable gland: M16, connecting terminal: 3 pole, precise PMMA optics, integral driver (AC/DC), CRI > 80, luminous flux: 140 lm, wattage: 3 W, delivered lumens 47 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,006 m², dimensions: Ø 75 mm, width 81 mm, weight 0.6 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08