



Multispot 1

8 221 446 049
0 W, 3000 K warm white,
medium wide beam plus 46°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, 2 tempered safety glasses: waterproof space for optical film and honeycomb louvres, dark screenprint, silicon gasket, closure with 2 stainless steel screws, mounting bracket: 1 elongated hole \varnothing 7 mm, spacing 18 mm, 1 centre hole \varnothing 8.5 mm, tilt range: 170°, cable gland: M20, connecting terminal: 3 pole, PMMA lens, integral driver (AC/DC), max 2 SDCM, service life L80/B10 > 50.000 h, Beam angle (FWHM): 46°, wattage: 0 W, protection type IP65, protection class I, impact resistance IK08, windage area 0,0139 m², dimensions (L×H×W): 153 × 185 × 133 mm, weight 1.4 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

Specification

Wattage	0 W	Beam angle (FWHM)	46°
Light source	LED 3000 K	Housing colour	black RAL 7021
Colour tolerance	max 2 SDCM	Power supply cable	\varnothing 6 – 13 mm
Lifetime ta 25° C	L80/B10 > 50.000 h	Protection type	IP65
Control gear	on / off	Protection class	I
Input voltage AC	220 – 240 V	Impact resistance	IK08
Input voltage DC	220 – 240 V	Windage area	0,0139m ²
Voltage protection	2 kV L/N 2 kV L/PE	Dimensions	153 × 185 × 133 mm
Luminaires per B16A / C16A	50 / 85	Weight	1,40 kg
		Max. ambient temperature ta	40°