



## Multispot 3

8 223 547 119

27 W, 2270 lm, 2700 K warm white, DALI, narrow beam 10°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, 2 tempered safety glasses: waterproof space for optical film and honeycomb louvres, dark screenprint, silicon gasket, closure with 2 stainless steel screws, mounting bracket: 2 drilled holes  $\varnothing$  7 mm, spacing 35 mm, 1 centre hole  $\varnothing$  17 mm, tilt range: 170°, cable gland: M20, connecting terminal: 5 pole, PMMA lens, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L80/B10 > 50.000 h, Beam angle (FWHM): 10°, luminous flux: 2270 lm, wattage: 27 W, delivered lumens 85 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,0284 m<sup>2</sup>, dimensions:  $\varnothing$  147 mm, width 190 mm, weight 2.6 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

## Specification

Wattage	27 W	Beam angle (FWHM)	10°
Delivered lumens	85 lm/W	Housing colour	black RAL 7021
Light source	LED 2700 K	Power supply cable	$\varnothing$ 6 – 13 mm
Color Rendering Index	CRI > 80	Protection type	IP65
Colour tolerance	max 2 SDCM	Protection class	I
Lifetime ta 25° C	L80/B10 > 50.000 h	Impact resistance	IK08
Control gear	DALI	Windage area	0,0284m <sup>2</sup>
Input voltage AC	220 – 240 V	Dimensions	$\varnothing$ 147 mm, width 190 mm
Input voltage DC	220 – 240 V	Weight	2,60 kg
Voltage protection	2 kV L/N   4 kV L/PE	Max. ambient temperature ta	35°
Luminaires per B16A / C16A	50 / 85		