







Nightspot B

8 952 164 009  
for ceramic metal halide lamps (HIT-CE)



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, closure with 4 stainless steel screws, powder coated aluminum mounting base adjustable: 2 drilled holes Ø 9 mm, spacing 105 mm, 1 centre hole Ø 22 mm, tilt range: 125°, cable gland: M20, connecting terminal: 3 pole, highly efficient anodized aluminum reflector, with built-in secondary reflector (narrow beam/medium wide beam) for optimal visual comfort and high efficiency, for glare control and reduction of spill light, integral ballast and ignitor, LPF, HPF available on request, Beam angle (FWHM): 7°, luminous flux: 9300 lm, wattage: 100 W, delivered lumens 86 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,05 m², dimensions: Ø 300 mm, width 280 mm, weight 6.2 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

IP65 IK08

Specification

|                  |          |                    |                        |
|------------------|----------|--------------------|------------------------|
| Wattage          | 100 W    | Beam angle (FWHM)  | 7°                     |
| Delivered lumens | 86 lm/W  | Housing colour     | white RAL 9002         |
| Control gear     | on / off | Power supply cable | Ø 8 – 15 mm            |
|                  |          | Protection type    | IP65                   |
|                  |          | Protection class   | I                      |
|                  |          | Impact resistance  | IK08                   |
|                  |          | Windage area       | 0,05m²                 |
|                  |          | Dimensions         | Ø 300 mm, width 280 mm |
|                  |          | Weight             | 6,20 kg                |