


Nightspot A₂

8 983 256 659 28 W, 2066 lm, 3000 K warm white, DALI, wide beam 53°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey , all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, closure with 4 stainless steel screws, for installation on poles Ø 60-100mm, adjustable aluminum mounting base, powder coated: 2 drilled holes Ø 9mm, spacing 105mm, 1 centre hole Ø 22mm, tilt range: 100°, cable gland: M20, connecting terminal: 5 pole, highly efficient anodized aluminum reflector, with built-in secondary reflector (narrow beam/medium wide beam) for optimal visual comfort and high efficiency, for glare control and reduction of spill light, inegral, dimmable driver (DALI), CRI > 80, max 2 SDCM,

service life L90/B10 > 50.000 h, Beam angle (FWHM): 53°, luminous flux: 2066 lm, wattage: 28 W, delivered lumens 75 lm/W, protection type IP67, protection class II, impact resistance IKo8, windage area 0,035 m², dimensions: Ø 180 mm, width 200 mm, weight 2.695 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



Beam angle (FWHM)	53°
Housing colour	silver grey
Power supply cable	Ø8–11 mm
Protection type	IP67
Protection class	II
Impact resistance	Іко8
Windage area	0,035m ²
Dimensions	Ø 180 mm, width 200 mm
Weight	2,70 kg
Max. ambient temperature ta	35°

Specification

opeemedaen			
Wattage	28 W	Beam angle (FWHM)	53°
Delivered lumens	75 lm/W	Housing colour	silve
Light source	led 3000 K	Power supply cable	Ø 8
Color Rendering Index	CRI > 80	Protection type	IP6;
Colour tolerance	max 2 SDCM	Protection class	Ш
Lifetime ta 25° C	L90/B10 > 50.000 h	Impact resistance	IKO
Control gear	DALI	Windage area	0,0
		Dimensions	۱ Ø
		\A/aiabt	0 7

Technical and formal changes reserved, product photos are exmplary. As of Willy Meyer+Sohn GmbH+Co. KG | Stemmessiepener Weg 5 | 58675 Hemer | Germany | info@meyer-lighting.com | www.meyer-lighting.com