





## **Nightspot B**

8 986 056 059 54 W, 4614 lm, 3000 K warm white, wide beam 64°







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## **Specification text**

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, closure with 4 stainless steel screws, powder coated aluminum mounting bracket with tilt scale: 2 drilled holes  $\varnothing$  9 mm, spacing 70 mm, 1 centre hole  $\varnothing$  22 mm, tilt range:  $135^{\circ}$ , cable gland: M20, connecting terminal: 3 pole, highly efficient anodized aluminum reflector, with built-in secondary reflector (narrow beam/medium wide beam) for optimal visual comfort and high efficiency, for glare control and reduction of spill light, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life Lgo/B10 > 50.000 h, Beam angle (FWHM): 64°, luminous flux: 4614 lm, wattage: 54 W, delivered lumens 85 lm/W, protection type IP67, protection class I, impact resistance IKo8, windage area 0,05  $\mathrm{m}^2$ , dimensions: Ø 240 mm, width 300 mm, weight 5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.





IP67 IK08

## Specification

Wattage 54 W Delivered lumens 85 lm/W Light source LED 3000 K Color Rendering Index CRI > 80 max 2 SDCM Colour tolerance Lifetime ta 25° C L90/B10 > 50.000 h on / off Control gear Input voltage AC 220 - 240 V Input voltage DC 195 - 255 V Voltage protection 4 kV L/N | 2 kV L/PE Luminaires per B16A / C16A 24/32

64° Beam angle (FWHM) Housing colour silver grey Power supply cable  $\emptyset$  8 - 15 mm Protection type IP67 Protection class Impact resistance **IK08** Windage area  $0.05m^{2}$ Dimensions Ø 240 mm, width 300 mm Weight 5,00 kg Max. ambient temperature ta 35°