


Nightspot B

8 952 251 079

For und ceramic metal halide lamps (HIT-CE)



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminium ALSi112, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, for installation on poles \varnothing 60-100mm, adjustable aluminium mounting base, powder coated: 2 drilled holes \varnothing 9mm, spacing 105mm, 1 centre hole \varnothing 22mm, tilt range: 80°, cable gland: M20, connecting terminal: 3 pole, highly efficient anodized aluminium reflector, with built-in secondary reflector (narrow beam/medium wide beam) for optimal visual comfort and high efficiency, for glare control and reduction of spill light, integral ballast and ignitor, LPF, HPF available on request, beam angle (FWHM): 8°, luminous flux: 6600 lm, wattage: 100 W, delivered lumens 75 lm/W, protection type IP65, protection class I, impact resistance IK08, windage area 0,05 m², dimensions: \varnothing 300 mm, width 280 mm, weight 5.8 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP65 IK08

Specification

Wattage 100 W
 Delivered lumens 75 lm/W
 Control gear on / off

Beam angle (FWHM) 8°
 Housing colour silver grey
 Power supply cable \varnothing 8 – 15 mm
 Protection type IP65
 Protection class I
 Impact resistance IK08
 Windage area 0,05m²
 Dimensions \varnothing 300 mm, width 280 mm
 Weight 5,80 kg
 Energy efficiency class A, A+