


Wall mount luminaire

8 894 066 009



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

housing made of corrosion-resistant die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: white RAL 9002, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, silicon gasket, polyester powder coated stainless steel release fastener, wall mounting plate: 2 drilled holes Ø 8.5 mm, spacing 120 mm, tilt range: 90°, cable gland: PG 13,5, connecting terminal: 3 pole, axially symmetrical high gloss aluminum reflector, integral electronic ballast, Beam angle (FWHM): 96° / 95°, wattage: 24 W, protection type IP54, protection class I, windage area 0,12 m², dimensions (L×H×W): 605 × 77 × 205 mm, weight 4.3 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP 54

Specification

| | | | |
|--------------|----------|-------------------|-------------------|
| Wattage | 24 W | Beam angle (FWHM) | 96° / 95° |
| Control gear | on / off | Housing colour | white RAL 9002 |
| | | Protection type | IP54 |
| | | Protection class | I |
| | | Windage area | 0,12m² |
| | | Dimensions | 605 × 77 × 205 mm |
| | | Weight | 4,30 kg |