


Superlight

8 824 148 009

For und



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

Specification text

polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, closure with 4 stainless steel screws, mounting bracket powder coated aluminum with tilt scale: 6 drilled holes \varnothing 10 mm, spacing 70 mm (120 mm, 200 mm), 1 centre hole \varnothing 22 mm, tilt range: 150°, cable gland: M20, connecting terminal: 3 pole, axially symmetrical high gloss aluminum reflector, integral ballast and ignitor, LPF, HPF available on request, Beam angle (FWHM): 23°, luminous flux: 55000 lm, wattage: 400 W, delivered lumens 122 lm/W, protection type IP65, protection class I, windage area 0,19 m², dimensions (L×H×W): 440 × 190 × 420 mm, weight 20 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.

 IP65

Specification

Wattage	400 W	Beam angle (FWHM)	23°
Delivered lumens	122 lm/W	Housing colour	black RAL 7021
Control gear	on / off	Power supply cable	\varnothing 8 – 15 mm
		Protection type	IP65
		Protection class	I
		Windage area	0,19m ²
		Dimensions	440 × 190 × 420 mm
		Weight	20,00 kg