



## Superlight LED 2

8 886 155 149

40 W, 3613 lm, 4000 K neutral white, DALI, asymmetrical 43  $^{\circ}$ 







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## **Specification text**

housing made of die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: silver grey, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, closure with 4 stainless steel screws, wall box: 2 drilled holes Ø 7 mm, spacing 110 mm, cable entry 7 - 10 mm, for recessed or surface mounted cable, tilt range: 200°, cable gland: M20, connecting terminal: 5 pole, highly efficient reflector, integral driver (DAII), CRI > 85, max 2 SDCM, service life L90/B10 > 50.000 h, luminous flux: 3613 lm, wattage: 40 W, delivered lumens 90 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area 0,047 m², dimensions (L×H×W): 215 × 110 × 250 mm, weight 4 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE mark.



IP67 IK08

## Specification

Wattage 40 W

Delivered lumens 90 lm/W

Light source LED 4000 K

Color Rendering Index CRI > 85

Colour tolerance max 2 SDCM

Lifetime ta 25° C L90/B10 > 50.000 h

Control gear DALI

Input voltage AC 220 - 240 VInput voltage DC 195 - 255 VVoltage protection 2 kV L/N | 4 kV L/PE

Luminaires per B16A / C16A 30 / 51

Housing colour silver grey

Power supply cable Ø 6 – 13 mm

Protection type IP67

Protection class I
Impact resistance IK08

Windage area 0,047m²

Dimensions  $215 \times 110 \times 250 \text{ mm}$ 

Weight 4,00 kg