



8 886 256 059

LED
4127 lm

Abstand/Distance	3 m	5 m	7 m	9 m	11 m	13 m
Beam Diameter (m)	7,4 m	12,4 m	17,4 m	22,3 m	27,3 m	32,2 m
Beam Height (m)	6,2 m	10,4 m	14,5 m	18,6 m	22,8 m	26,9 m
Beam Spread (lx)	77 lx	28 lx	14 lx	9 lx	6 lx	4 lx



Specification text

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



IP 67 IK08

Specification

Wattage	40 W	Beam angle (FWHM)	92° / 102°
Delivered lumens	102 lm/W	Housing colour	silver grey
Light source	LED 3000 K	Power supply cable	Ø 6 – 13 mm
Color Rendering Index	CRI > 80	Protection type	IP67
Colour tolerance	max 2 SDCM	Protection class	I
Lifetime ta 25° C	L90/B10 > 50.000 h	Impact resistance	IK08
Control gear	on / off	Windage area	0,047m²
Input voltage AC	220 – 240 V	Dimensions	215 × 70 × 215 mm
Input voltage DC	195 – 255 V	Weight	3,20 kg
Voltage protection	4 kV L/N 2 kV L/PE	Max. ambient temperature ta	40°
Luminaires per B16A / C16A	30 / 51		