







## Superlight Nano 3

8 819 046 429

9 × 2,4 W, 1596 lm, 3000 K warm white,  
linear vertical 41° / 7°



Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## Specification text

housing made of die-cast aluminum AlSi12, polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass, anti-reflective coating from 1 side, dark screenprint, silicon gasket, powder coated die cast zinc mounting bracket with tilt scale: 2 drilled holes Ø 9 mm, spacing 60 mm, 1 centre hole Ø 13 mm, tilt range: 120°, cable gland: 2 x M20, cable entry: 2, connecting terminal: 3 pole, highly efficient optics made of transparent thermoplastic for precise lighting tasks, integral driver (AC/DC), CRI > 80, max 2 SDCM, service life L90/B10 > 50.000 h, Beam angle (FWHM): 41° / 7°, luminous flux: 1596 lm, wattage: 22 W, delivered lumens 73 lm/W, protection type IP67, protection class I, impact resistance IK08, windage area 0,013 m², dimensions (L×H×W): 115 × 95 × 115 mm, weight 1.5 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.



IP 67 IK08

## Specification

|                            |                      |                             |                   |
|----------------------------|----------------------|-----------------------------|-------------------|
| Wattage                    | 22 W                 | Beam angle (FWHM)           | 41° / 7°          |
| Delivered lumens           | 73 lm/W              | Housing colour              | black RAL 7021    |
| Light source               | LED 3000 K           | Power supply cable          | Ø 6 – 13 mm       |
| Color Rendering Index      | CRI > 80             | Protection type             | IP67              |
| Colour tolerance           | max 2 SDCM           | Protection class            | I                 |
| Lifetime ta 25° C          | L90/B10 > 50.000 h   | Impact resistance           | IK08              |
| Control gear               | on / off             | Windage area                | 0,013m²           |
| Input voltage AC           | 100 – 277 V          | Dimensions                  | 115 × 95 × 115 mm |
| Input voltage DC           | 105 – 277 V          | Weight                      | 1,50 kg           |
| Voltage protection         | 2 kV L/N   4 kV L/PE | Max. ambient temperature ta | 35°               |
| Luminaires per B16A / C16A | 69 / 81              |                             |                   |