





## Uplight 180

8 655 015 149 11 W, 893 lm, 4000 K neutral white, DALI, medium wide beam, adjustable 31°







Customized solutions and modifications are possible: Special RAL, DB or NCS colours as polyester powder coat, luminaires in 2700 K and other colour temperatures and versions for high ambient temperature.

## **Specification text**

housing of corrosion-resistant die-cast aluminum AlSi12, double polyester powder coated by high-quality and UV-stabilized coating process, Colour: black RAL 7021, all exterior parts are stainless steel, tempered safety glass flush with frame, anti-reflective coating from 1 side, dark screenprint, for loads up to max. 5000 kg (according to IEC / EN 60598-2-13), silicon gasket, cover frame and closure with 6 stainless steel screws, cable gland: M20, connecting terminal: 5 pole, highly efficient faceted rotationally symmetrical reflector, lockable, tilt range: 0-15°, lockable, 0,8 m cable Ho7RN-F5G1, integral driver (DALI), CRI > 80, max 3 SDCM, service life L90/B10 > 50.000 h, Beam angle (FWHM): 31°, luminous flux: 893 lm, wattage: 11 W, delivered lumens 81 lm/W, protection type IP68, protection class I, impact resistance IK10, dimensions: Ø 180 mm, width 152 mm, weight 2.6 kg

The modular luminaire design makes the replacement of components possible. The product meets the demands of the applicable EU guidelines and product safety regulations and bears the CE and ENEC marks.





IP 68 IK 10

## Specification

Wattage

1 1 W

Delivered lumens

8 1 lm/W

Light source

LED 4000 K

Color Rendering Index

Colour tolerance

max 3 SDCM

Lifetime ta 25° C

L90/B10 > 50.000 h

Control gear

DALI

Beam angle (FWHM) 31°
Housing colour black RAL 7021
Protection type IP68

Protection class I
Impact resistance IK10

Dimensions Ø 180 mm, width 152 mm

Weight 2,60 kg
Max. ambient temperature ta 35°